

Öffnungsüberwachung Opening state monitoring

Einbau-/Aufbaumagnetkontakt LSA-Schneidklemmtechnik geeignet.

Recess/surface mount magnetic contact suitable for insulation displacement technology LSA.



Technische Daten Specifications	
Kontaktart Contact type	1-poliger Schließer single-pole NO contact
Betriebsspannung Power input	max. 40 V DC
Schaltstrom Switching current	max. 500 mA
Kontaktbelastbarkeit Contact capacity	max. 6 W
Anschlusskabel Connecting cable	LIYY 2 x 0,14 mm ² , Cu verzinkt LIYY 2 x 0.14 mm ² , Cu tinned
Innenleiter Inner conductor	weiß white
Maße Kabel Cable dimensions	L 2 m, Ø 3,2 mm L 2 m, Ø 3.2 mm
Kontakt Contact	Ø 8 x 31 mm
Magnet Magnet	Ø 6 x 30 mm AlNiCo, axial polarisiert Ø 6 x 30 mm AlNiCo, axial polarized
Kunststoffrohr Plastic tube	Ø 8 x 31 mm für Magnet Ø 8 x 31 mm for magnet
EF 8/10	2 Einbauflansche für Magnet und Kontakt; für Holz, Kunststoff, Aluminium und nichtmagnetische Metalle 2 recess mount flanges for magnet and contact; suitable for wood, plastic, aluminium and non-ferromagnetic metals
Befestigungsschrauben Fastening screws	4 St., DIN 7982 - 2,9 x 13 - V 2 A 4 pcs., DIN 7982 - 2.9 x 13 - V 2 A
Material Kunststoffteile Housing material	PBT-GF, S-B oder A-B-S PBT-GF, S-B or A-B-S
Temperaturbereich Temperature range	-25 °C bis +70 °C -25 °C to +70 °C
Schutzart Protection category	VdS-Umweltklasse III, IP 67 VdS-Environmental Class III, IP 67